



SYNTH MOTOR OIL

COLUMBUS RACING SAE 0W30 SM/CF COLUMBUS RACING SAE 0W40 SM/CF COLUMBUS RACING SAE 0W50 SM/CF

Packages:, 20X1LT,4X4LT, 4X5LT, 20LT, 200 LT, 208LT, 1000 LT

Multi-grade oil with synthetic base, it has been specially developed for all modern turbocharged, high output gasoline and diesel engines of passenger cars, SUVs , light vans and trucks. The synthetic bases adopted and the choice of the most modern additives give to the product a particular thermo stability warranting low wastes and an excellent performance into severe conditions of exercise of the engine. The high index of viscosity give it suitable for every climatic and seasonal conditions warranting, at the same time, the greatest protection to engine both in cold starting and long distances. The product is particularly indicated for multi-valves and turbo-compressed engines with high power. This oils are designed to exceed the latest industry specifications and the major car manufacturers' service fill requirements.

			0W30	0W40	0W50
Density at 15°C	ISO 3675, ASTM D1298	kg/lt	>0.860	> 0.860	> 0.860
Flash point	ISO 2592, ASTM D92	°C	> 200	> 200	> 200
Cinematic viscosity at 100 °C	ISO 3104, ASTM D445	cSt	9.3-12.5	12.5-16.3	16.3-21.9
Viscosity index	ISO 2909, ASTM D2270		165	150	179
Pour point	ISO 3016, ASTM D97	C	- 36	- 36	- 32
T. B. N.	ASTM 2896	mgKOH/g	10	10	10
Sulphated Ash % wt	ASTM D 874		1,26	1,26	1,26

Performances: API SM/CF, ACEA A3/B3/C3/B4, VW 505.00/507.00, MB 229.3, BMW (LL01-C3)