

COLUMBUS SYNTH 5W/20 SN

Packaging: 12X1 LT, 4X4 LT, 4X5 LT, 20 LT, 60 LT, 200 LT, 1000 LT

COLUMBUS SYNTH 5W/20 SN fully synthetic base oil has been specially developed for all modern EURO 6 engines of the new generation and with FUEL ECONOMY properties. The synthetic bases adopted and the choice of the most modern additives give the product a particular thermal stability that guarantees low waste and excellent performance in extreme engine operating conditions. The high viscosity index makes it suitable for all climatic and seasonal conditions while ensuring maximum engine protection both in cold starts and over long distances. These oils are designed to exceed the latest industry specifications and meet the filling requirements of the main car manufacturers.

PROPERTIES:

- synthetic oil with high viscosity index; - excellent detergent characteristics;
- excellent cold dispersion;
- very high stability, which helps reduce consumption while maintaining along the characteristics of the oil, even after prolonged periods of use;
- excellent protection against the formation of low and high temperature deposits
- temperature, against wear, rust, corrosion and foam;
- low pour point;
- reduces oil consumption

TYPICAL CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	UM	VALUES
Density at 15°C	ISO 3675, ASTM D1298	kg/ lt	>0.848
Flash point	ISO 2592, ASTM D92	°C	> 215
Viscosity kinematics at 40°C	ISO 3104, ASTM D445	cSt	43.5
Viscosity kinematics at 100°C	ISO 3104, ASTM D445	cSt	8
Viscosity index	ISO 2909, ASTM D2270		158
Pour point	ISO 3016, ASTM D97	°C	-36

Specifications : SAE 5W/20, API SN, ACEA C5, FORD WSS -M2C948-B, STJLR.03.5004



Columbia Italian Society of Lubricants and Related Products Srl
Via Burba 8, 16163 Genoa, Italy.
Fiscal Code 00262110109 VAT No. 00262110109
Tel. 010 71.00.33
columbia@columbiamotoroil.com
www.columbiamotoroil.com
PEC columbia.lube@pcert.postecert.it

