RECORD SAE 50 CLASSIC SC/CC

Packaging: 12X1 LT, 4X4 LT, 4X5 LT, 20 LT, 60 LT, 200 LT, 1000 LT

High-quality unigrade lubricant for diesel and petrol engines of historic cars. This lubricant is formulated according to modern detergent technology, but respecting historic motoring standards. Formulated with special additives to give high performance and protection even at high temperatures.

PROPERTIES:

- High viscosity index. to ensure greater resistance to higher temperatures, and minimal viscosity variations at various temperatures, despite high stresses
- Good cleaning-dispersing power, to counteract the formation of sludge, lacquer, resins and corrosive compounds, especially when high-sulphur gas oils are used.
- Alkalinity reserve that protects even the most delicate engine parts from corrosion.
- Low ash content.
- Anti-wear characteristics to reduce wear on mechanical parts;
- Anti-rust, anti-oxidation and anti-foam power.

TYPICAL CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	UM	VALUES
Density at 15°C	ISO 3675, ASTM D1298	kg/lt	>0.880
Flash point	ISO 2592, ASTM D92	°C	> 230
Kinematic viscosity at 40°C	ISO 3104, ASTM D445	cSt	255.0
Kinematic viscosity at 100°C	ISO 3104, ASTM D445	cSt	21.0
Viscosity index	ISO 2909, ASTM D2270		95
Sliding point	ISO 3016, ASTM D97	°C	-27

Specifications: SAE 50, API SC/CC.

Columbia Società Italiana Lubrificanti e Affini S.r.l.
Via Burba 8, 16163 Genoa, Italy.
Fiscal Code 00262110109 VAT No.
Tel. 010 71.00.33
columbia@columbiamotoroil.com
www.columbiamotoroil.com
PEC columbia.lube@pcert.postecert.it

COLUMBIA
Motor Oil Company
Since 1934