

GEAR OIL 90 GL5

Packaging: 12X1 LT, 4X4 LT, 4X5 LT, 20 LT, 60 LT, 200 LT, 1000 LT

A mineral lubricant of a paraffinic nature for gears, gearboxes and differentials, formulated with highly refined bases and an additive specifically selected for gear lubrication.

PROPERTIES

- Excellent anti-wear and anti-corrosion properties, extends transmission life;
- Excellent protection against low and high temperature deposit formation, wear, rust, corrosion and foam;
- Low sliding point;

TYPICAL CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	UM	VALUES
Density at 15°C	ISO 3675, ASTM D1298	kg/lt	>0.883
Flash point	ISO 2592, ASTM D92	°C	> 210
Kinematic viscosity at 40°C	ISO 3104, ASTM D445	cSt	190.0
Kinematic viscosity at 100°C	ISO 3104, ASTM D445	cSt	17.0
Viscosity index	ISO 2909, ASTM D2270		100
Sliding point	ISO 3016, ASTM D97	°C	-30

Specifications: SAE 90, API GL5.



Columbia Società Italiana Lubrificanti e Affini S.r.l.

Via Burba 8, 16163 Genoa, Italy.

Fiscal Code 00262110109 VAT No.

Tel. 010 71.00.33

columbia@columbiamotoroil.com

www.columbiamotoroil.com

PEC columbia.lube@pcert.postecert.it

