GRASSO AL LITIO A-M 2000 E.P. 2

Packages: 12X1 KG,4X4,5 KG, 18 KG, 190 KG

GRASSO AL LITIO A-M 2000 E.P. 2 is a superior quality grease, with a creamy appearance, light in colour; appropriately added with EP (Extreme Pressure), featuring excellent mechanical stability, excellent resistance to oxidation, ageing and the washing action of water, it can be used in a wide operating range (from -20°C to +120 °C).

Given its peculiar properties, GRASSO AL LITIO A-M 2000 E.P. 2 individually replaces any type of grease (calcium, sodium, aluminium and mixed-based) and can be used in the most varied applications: lubrication of flat or rolling bearings of industrial, construction and road machinery and in general when operating conditions characterised by high speeds, high temperatures (up to 120° C) and/or the presence of water occur simultaneously.

PROPERTIES

- The appropriate EP additive provides the sulphur-phosphorus combination to ensure performance at high speeds, or at low speeds with high loads, such as to ensure the persistence of the lubricating film in all particularly severe operating conditions;
- High resistance to oxidation;
- High resistance to corrosion and rust.

TYPICAL CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	UM	VALUES
Color, Appearance	-	-	Amber, Pomatoso
Base oil	-	-	Mineral
Base type	-	-	Lithium
Base oil viscosity at 40°C	ASTM D-445	Cst	ISO VG 150
Dropping point	ASTM D-566	°C	180
Thermal limit of use	-	°C	-20°C + 120°C
NLGI consistency grade	-	NGLI	2

Columbia Italian Society of Lubricants and Related Products Srl
Via Burba 8, 16163 Genoa, Italy.
Fiscal Code 00262110109 VAT No. 00262110109
Tel. 010 71.00.33
columbia@columbiamotoroil.com
www.columbiamotoroil.com
PEC columbia.lube@pcert.postecert.it

COLUMBIA
Motor Oil Company
Since 1934