GRASSO MOLIB 2

Packages: 12X1 KG,4X4,5 KG, 18 KG, 190 KG

Special lithium grease containing graphite and molybdenum disulfide, EP additives, anti-wear and anti-rust. Adhesive, water-repellent, anti-corrosion, anti-wear characteristics, even in severe operating conditions. Suitable for lubricating earthmoving machines, crushers, quarries, agricultural machinery, construction and road machinery, heavy industry machinery and for the lubrication of joints, pins, bushings, sliding surfaces, guides, fifth wheels, bearings.
Perfect for use in EP (extreme pressure) conditions; outstanding adhesion, water repellency, anti-corrosion, anti-wear and prolonged lubrication film properties.

PROPERTIES

- Versatile and multipurpose grease
- High degree of corrosion protection
- Extreme pressure and anti-wear performance for protection under load
- Wide operating temperature range: -20°C to +140°C

TYPICAL CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	UM	VALUES
Color, Appearance	-	-	Black, Pseudoplastic mass
Base oil	-	-	Mineral
Nature of soap	-	-	Lithium hydroxide
Base oil viscosity at 40°C	ASTM D445	Cst	> 600
Dropping point	ASTM D-566	°C	220
Operating temperature	-	°C	-20ºC and +140ºC
NLGI consistency grade	-	-	2

Columbia Italian Society of Lubricants and Related Products Srl
Via Burba 8, 16163 Genoa, Italy.
Fiscal Code 00262110109 VAT No. 00262110109
Tel. 010 71.00.33
columbia@columbiamotoroil.com
www.columbiamotoroil.com
PEC columbia.lube@pcert.postecert.it

COLUMBIA
Motor Oil Company
Since 1934