TECHNO 110

Packaging: 12X1 LT, 4X4 LT, 4X5 LT, 20 LT, 60 LT, 200 LT, 1000 LT

Highly refined mineral white oil suitable for all applications requiring a non-medicinal degree of purity.

USES

- Chemical Industry : as an internal plasticizer for rubber compounds , in the preparation of plastic materials, to facilitate mold release.
- Mechanical Industry: in the processing of light metals, in precision mechanisms in watchmaking, in firearms.
- Textile industry: as an oleating agent for artificial fibres, knitted nylon, for sewing machines and knitting machines, for spinning, knitting weaving.
- Cosmetics and Perfumery Industry
- Glass Industry

TYPICAL CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	UM	VALUES
Density at 20°C	ISO 3675, ASTM D1298	kg/ lt	>0.870
Flash point	ISO 2592, ASTM D92	°C	> 190
Viscosity kinematics at 40°C	ISO 3104, ASTM D445	cSt	15.0
Viscosity kinematics at 100°C	ISO 3104, ASTM D445	cSt	-
Solubility in water	-	-	Not soluble
Odor	-	-	Sui generis

Specifications : USF and DA Regulation n° 178.3620 (b).

Columbia Italian Society of Lubricants and Related Products Srl
Via Burba 8, 16163 Genoa, Italy.
Fiscal Code 00262110109 VAT No. 00262110109
Tel. 010 71.00.33
columbia@columbiamotoroil.com
www.columbiamotoroil.com
PEC columbia.lube@pcert.postecert.it

COLUMBIA
Motor Oil Company
Since 1934